

ENZO SERIES

INNOVATIVE SOLUTIONS FOR TOURING, RENTAL & STAGING AND BROADCAST

ENZO

MODEL	ENZO 3/3V/3H/3Q	ENZO 4/4V/4H/4Q	ENZO 5/5V/5H/5Q
Pixel Pitch	3.9mm	4.6mm	5.9mm
Scan Ratio	1/8	1/6	1/7
LED Configuration	SMD1415 Black	SMD1921 Black	SMD1921 Black
Max Brightness Calibrated	4,500nits	5,000nits	5,000nits
Panel Dimension	1,000mm x 1,000mm 1,000mm x 500mm(H) 500mm x 1,000mm(V) 500mm x 500mm(Q)	1,000mm x 1,000mm 1,000mm x 500mm(H) 500mm x 1,000mm(V) 500mm x 500mm(Q)	1,000mm x 1,000mm 1,000mm x 500mm(H) 500mm x 1,000mm(V) 500mm x 500mm(Q)
Panel Resolution (H x V)	256 x 256 256 x 128(H) 128 x 256(V) 128 x 128(Q)	216 x 216 216 x 108(H) 108 x 216(V) 108 x 108(Q)	168 x 168 168 x 84(H) 84 x 168(V) 84 x 84(Q)
Power Consumption Max/Average	750W / 250W 400W / 140W(H) 400W / 140W(V) 200W / 70W(Q)	750W / 250W 400W / 140W(H) 400W / 140W(V) 200W / 70W(Q)*	750W / 250W 400W / 140W(H) 400W / 140W(V) 200W / 70W(Q)
Viewing Horizontal	160°	160°	160°
Viewing Vertical	140°	140°	140°
Refresh Rate	7,680Hz	7,680Hz	7,680Hz
Gray Scale	16bit	16bit	16bit
Transparency	Solid	Solid	Solid
Serviceability	Front / Rear	Front / Rear	Front / Rear
Curving (Concave & Convex)	Concave 15° ~ Convex 9°	Concave 15° ~ Convex 9°	Concave 15° ~ Convex 9°
Panel Weight(With Windbrace)	34kg, 21kg(H), 20kg(V), 10kg(Q)	34kg, 21kg(H), 20kg(V), 10kg(Q)	34kg, 21kg(H), 20kg(V), 10kg(Q)
Max. Hanging (panels)	20	20	20
Max. Stacking (panels)	6	6	6
Frame Material	Magnesium Alloy & Aluminium Alloy	Magnesium Alloy & Aluminium Alloy	Magnesium Alloy & Aluminium Alloy
Processing Platform	Brompton / NovaStar 5G	Brompton / NovaStar 5G	Brompton / NovaStar 5G
Operation Temp/Humidity	-20°~+50 / 10~90%RH	-20°~+50 / 10~90%RH	-20°~+50 / 10~90%RH
IP Rating	IP65	IP65	IP65
Certifications	CE, ETL, FCC, RoHS, WEEE	CE, ETL, FCC, RoHS, WEEE	CE, ETL, FCC, RoHS, WEEE

Visit our website for more information



PIXREAL.EU

ENZO SERIES the ultimate solution for both indoor and outdoor (live) events. Designed for tours, festivals, and outdoor stages, it combines smart engineering with efficiency to give event organizers, AV rental companies and crews, as well as production professionals the premium LED panels they need. It is designed to withstand 48KG of side impact, meaning its ideal for high pressure and high demanding environments including Touring Productions and Festivals Without compromising the quality that will wow your audience.

